



## Electrical Dry Contacts Cleaner 200 ml (M202)

Spray product suitable for cleaning and maintenance of electrical, electromagnetic and electronic contacts. It removes greasy substances and moisture from the surface.



Quantity	200 ml
Barcode	EAN 13: 8034108893778
Box / Case	12 pz

**ELECTRICAL DRY CONTACTS CLEANER** – Specifically formulated for the deep cleaning of electrical, electronic, and electromagnetic contacts. It immediately removes humidity and oily substances such as grease, oil, sludge, wax and glue from the surface, leaving it clean and degreased. The product might be corrosive to certain delicate surfaces.

### Technical Specifications:

Aspect	Tin-Plate can under pressure fluid
Color	Transparent
Odour	Characteristic of solvent
Relative density	at 20°C 0,60 ÷ 0,64 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Steam tension	at 20°C: 250 hPa
Viscosity at 25°C	0,700 mm <sup>2</sup> /s SIO D445 (ASTM D445)
Dry point	415°C
Observations	Flammable, not to use on tension facilities

**HOW TO USE:** Shake Well. Spray directly on surface to be treated from a distance of about 20 cm. Do not apply to equipment in tension. Do not apply to overheated materials. Turn on power only after the complete evaporation of the product. Allow time to dry.

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

**BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT**